

	Part #		Invert Depth				Overall Depth				Volume	Weight
	K100	KS100	in		mm		in		mm		gal	lbs
			female	male	female	male	female	male	female	male		
K1-00 Constant depth channel - 39.37" (1 m)*	74041	74441	3.94	3.94	100	100	4.72	4.72	120	120	1.96	28.1
K1-1 Sloped channel - 39.37" (1 m)	74001	74401	3.94	4.13	100	105	4.72	4.92	120	125	1.99	28.1
K1-2 Sloped channel - 39.37" (1 m)	74002	74402	4.13	4.33	105	110	4.92	5.12	125	130	2.04	28.9
K1-3 Sloped channel - 39.37" (1 m)	74003	74403	4.33	4.53	110	115	5.12	5.31	130	135	2.13	29.7
K1-4 Sloped channel - 39.37" (1 m)	74004	74404	4.53	4.72	115	120	5.31	5.51	135	140	2.23	30.5
K1-5 Sloped channel - 39.37" (1 m)*	74005	74405	4.72	4.92	120	125	5.51	5.71	140	145	2.33	31.3
K1-6 Sloped channel - 39.37" (1 m)	74006	74406	4.92	5.12	125	130	5.71	5.91	145	150	2.43	32.1
K1-7 Sloped channel - 39.37" (1 m)	74007	74407	5.12	5.31	130	135	5.91	6.10	150	155	2.54	32.9
K1-8 Sloped channel - 39.37" (1 m)	74008	74408	5.31	5.51	135	140	6.10	6.30	155	160	2.65	33.7
K1-9 Sloped channel - 39.37" (1 m)	74009	74409	5.51	5.71	140	145	6.30	6.50	160	165	2.75	34.5
K1-10 Sloped channel - 39.37" (1 m)*	74010	74410	5.71	5.91	145	150	6.50	6.69	165	170	2.86	35.3
K1-010 Constant depth channel - 39.37" (1 m)*	74043	74443	5.91	5.91	150	150	6.69	6.69	170	170	2.85	35.3
K1-0103 Constant depth channel - 19.69" (0.5 m)*	74044	74444	5.91	5.91	150	150	6.69	6.69	170	170	1.43	17.0
K1-11 Sloped channel - 39.37" (1 m)	74011	74411	5.91	6.10	150	155	6.69	6.89	170	175	2.97	36.1
K1-12 Sloped channel - 39.37" (1 m)	74012	74412	6.10	6.30	155	160	6.89	7.09	175	180	3.08	36.9
K1-13 Sloped channel - 39.37" (1 m)	74013	74413	6.30	6.50	160	165	7.09	7.28	180	185	3.19	37.7
K1-14 Sloped channel - 39.37" (1 m)	74014	74414	6.50	6.69	165	170	7.28	7.48	185	190	3.30	38.5
K1-15 Sloped channel - 39.37" (1 m)*	74015	74415	6.69	6.89	170	175	7.48	7.68	190	195	3.42	39.3
K1-16 Sloped channel - 39.37" (1 m)	74016	74416	6.89	7.09	175	180	7.68	7.87	195	200	3.53	40.1
K1-17 Sloped channel - 39.37" (1 m)	74017	74417	7.09	7.28	180	185	7.87	8.07	200	205	3.64	40.9
K1-18 Sloped channel - 39.37" (1 m)	74018	74418	7.28	7.48	185	190	8.07	8.27	205	210	3.75	41.7
K1-19 Sloped channel - 39.37" (1 m)	74019	74419	7.48	7.68	190	195	8.27	8.46	210	215	3.86	42.5
K1-20 Sloped channel - 39.37" (1 m)*	74020	74420	7.68	7.87	195	200	8.46	8.66	215	220	3.98	43.4
K1-020 Constant depth channel - 39.37" (1 m)*	74045	74445	7.87	7.87	200	200	8.66	8.66	220	220	3.97	43.4
K1-0203 Constant depth channel - 19.69" (0.5 m)*	74046	74446	7.87	7.87	200	200	8.66	8.66	220	220	1.98	20.5
K1-21 Sloped channel - 39.37" (1 m)	74021	74421	7.87	8.07	200	205	8.66	8.86	220	225	4.09	44.2
K1-22 Sloped channel - 39.37" (1 m)	74022	74422	8.07	8.27	205	210	8.86	9.06	225	230	4.20	45.0
K1-23 Sloped channel - 39.37" (1 m)	74023	74423	8.27	8.46	210	215	9.06	9.25	230	235	4.32	45.8
K1-24 Sloped channel - 39.37" (1 m)	74024	74424	8.46	8.66	215	220	9.25	9.45	235	240	4.42	46.6
K1-25 Sloped channel - 39.37" (1 m)*	74025	74425	8.66	8.86	220	225	9.45	9.65	240	245	4.54	47.4
K1-26 Sloped channel - 39.37" (1 m)	74026	74426	8.86	9.06	225	230	9.65	9.84	245	250	4.66	48.2
K1-27 Sloped channel - 39.37" (1 m)	74027	74427	9.06	9.25	230	235	9.84	10.04	250	255	4.78	49.0
K1-28 Sloped channel - 39.37" (1 m)	74028	74428	9.25	9.45	235	240	10.04	10.24	255	260	4.89	49.8
K1-29 Sloped channel - 39.37" (1 m)	74029	74429	9.45	9.65	240	245	10.24	10.43	260	265	5.00	50.6
K1-30 Sloped channel - 39.37" (1 m)*	74030	74430	9.65	9.84	245	250	10.43	10.63	265	270	5.11	51.4
K1-030 Constant depth channel - 39.37" (1 m)*	74047	74447	9.84	9.84	250	250	10.63	10.63	270	270	5.10	51.4
K1-0303 Constant depth channel - 19.69" (0.5 m)*	74048	74448	9.84	9.84	250	250	10.63	10.63	270	270	2.55	24.0
K1-31 Sloped channel - 39.37" (1 m)	74031	74431	9.84	10.04	250	255	10.63	10.83	270	275	5.23	52.2
K1-32 Sloped channel - 39.37" (1 m)	74032	74432	10.04	10.24	255	260	10.83	11.02	275	280	5.34	53.0
K1-33 Sloped channel - 39.37" (1 m)	74033	74433	10.24	10.43	260	265	11.02	11.22	280	285	5.45	53.8
K1-34 Sloped channel - 39.37" (1 m)	74034	74434	10.43	10.63	265	270	11.22	11.42	285	290	5.56	54.6
K1-35 Sloped channel - 39.37" (1 m)*	74035	74435	10.63	10.83	270	275	11.42	11.61	290	295	5.68	55.4
K1-36 Sloped channel - 39.37" (1 m)	74036	74436	10.83	11.02	275	280	11.61	11.81	295	300	5.79	56.2
K1-37 Sloped channel - 39.37" (1 m)	74037	74437	11.02	11.22	280	285	11.81	12.01	300	305	5.91	57.0
K1-38 Sloped channel - 39.37" (1 m)	74038	74438	11.22	11.42	285	290	12.01	12.20	305	310	6.02	57.9
K1-39 Sloped channel - 39.37" (1 m)	74039	74439	11.42	11.61	290	295	12.20	12.40	310	315	6.13	58.7
K1-40 Sloped channel - 39.37" (1 m)*	74040	74440	11.61	11.81	295	300	12.40	12.60	315	320	6.25	59.5
K1-040 Constant depth channel - 39.37" (1 m)*	74049	74449	11.81	11.81	300	300	12.60	12.60	320	320	6.24	59.5
K1-0403 Constant depth channel - 19.69" (0.5 m)*	74050	74450	11.81	11.81	300	300	12.60	12.60	320	320	3.12	27.5

Notes:

1. K100 has a galvanized steel edge rail for general use. KS100 has a grade 304 stainless steel edge rail for use where increased aesthetics or corrosion resistance is required.
2. KlassikDrain is sold as channel only.

* This channel features bottom knockouts; 4" & 6" for 100 mm channels.