

	Part No.		Invert Depth				Overall Depth				Volume	Weight
	K200	KS200	in		mm		in		mm		gal	lbs
			female	male	female	male	female	male	female	male		
<b>K2-00 Constant depth channel - 39.37" (1 m)</b>	<b>75041</b>	<b>75441</b>	<b>7.87</b>	<b>7.87</b>	<b>200</b>	<b>200</b>	<b>8.86</b>	<b>8.86</b>	<b>225</b>	<b>225</b>	<b>7.54</b>	<b>83.6</b>
K2-1 Sloped channel - 39.37" (1 m)	75001	75401	7.87	8.07	200	205	8.86	9.06	225	230	7.94	83.6
K2-2 Sloped channel - 39.37" (1 m)	75002	75402	8.07	8.27	205	210	9.06	9.25	230	235	8.13	84.7
K2-3 Sloped channel - 39.37" (1 m)	75003	75403	8.27	8.46	210	215	9.25	9.45	235	240	8.33	85.8
K2-4 Sloped channel - 39.37" (1 m)	75004	75404	8.46	8.66	215	220	9.45	9.65	240	245	8.53	86.9
K2-5 Sloped channel - 39.37" (1 m)	75005	75405	8.66	8.86	220	225	9.65	9.84	245	250	8.74	88.0
K2-6 Sloped channel - 39.37" (1 m)	75006	75406	8.86	9.06	225	230	9.84	10.04	250	255	8.95	89.1
K2-7 Sloped channel - 39.37" (1 m)	75007	75407	9.06	9.25	230	235	10.04	10.24	255	260	9.16	90.2
K2-8 Sloped channel - 39.37" (1 m)	75008	75408	9.25	9.45	235	240	10.24	10.43	260	265	9.37	91.3
K2-9 Sloped channel - 39.37" (1 m)	75009	75409	9.45	9.65	240	245	10.43	10.63	265	270	9.58	92.4
K2-10 Sloped channel - 39.37" (1 m)	75010	75410	9.65	9.84	245	250	10.63	10.83	270	275	9.79	93.5
<b>K2-010 Constant depth channel - 39.37" (1 m)</b>	<b>75043</b>	<b>75443</b>	<b>9.84</b>	<b>9.84</b>	<b>250</b>	<b>250</b>	<b>10.83</b>	<b>10.83</b>	<b>275</b>	<b>275</b>	<b>9.59</b>	<b>93.5</b>
<b>K2-0103 Constant depth channel - 19.69" (0.5 m)</b>	<b>75044</b>	<b>75444</b>	<b>9.84</b>	<b>9.84</b>	<b>250</b>	<b>250</b>	<b>10.83</b>	<b>10.83</b>	<b>275</b>	<b>275</b>	<b>4.80</b>	<b>56.0</b>
K2-11 Sloped channel - 39.37" (1 m)	75011	75411	9.84	10.04	250	255	10.83	11.02	275	280	10.01	94.6
K2-12 Sloped channel - 39.37" (1 m)	75012	75412	10.04	10.24	255	260	11.02	11.22	280	285	10.22	95.7
K2-13 Sloped channel - 39.37" (1 m)	75013	75413	10.24	10.43	260	265	11.22	11.42	285	290	10.44	96.8
K2-14 Sloped channel - 39.37" (1 m)	75014	75414	10.43	10.63	265	270	11.42	11.61	290	295	10.66	97.9
K2-15 Sloped channel - 39.37" (1 m)	75015	75415	10.63	10.83	270	275	11.61	11.81	295	300	10.88	99.0
K2-16 Sloped channel - 39.37" (1 m)	75016	75416	10.83	11.02	275	280	11.81	12.01	300	305	11.10	100.1
K2-17 Sloped channel - 39.37" (1 m)	75017	75417	11.02	11.22	280	285	12.01	12.20	305	310	11.32	101.2
K2-18 Sloped channel - 39.37" (1 m)	75018	75418	11.22	11.42	285	290	12.20	12.40	310	315	11.54	102.3
K2-19 Sloped channel - 39.37" (1 m)	75019	75419	11.42	11.61	290	295	12.40	12.60	315	320	11.76	103.4
K2-20 Sloped channel - 39.37" (1 m)	75020	75420	11.61	11.81	295	300	12.60	12.80	320	325	11.98	104.5
<b>K2-020 Constant depth channel - 39.37" (1 m)</b>	<b>75045</b>	<b>75445</b>	<b>11.81</b>	<b>11.81</b>	<b>300</b>	<b>300</b>	<b>12.80</b>	<b>12.80</b>	<b>325</b>	<b>325</b>	<b>11.78</b>	<b>104.5</b>
<b>K2-0203 Constant depth channel - 19.69" (0.5 m)</b>	<b>75046</b>	<b>75446</b>	<b>11.81</b>	<b>11.81</b>	<b>300</b>	<b>300</b>	<b>12.80</b>	<b>12.80</b>	<b>325</b>	<b>325</b>	<b>5.89</b>	<b>64.0</b>
K2-21 Sloped channel - 39.37" (1 m)	75021	75421	11.81	12.01	300	305	12.80	12.99	325	330	12.21	105.6
K2-22 Sloped channel - 39.37" (1 m)	75022	75422	12.01	12.20	305	310	12.99	13.19	330	335	12.42	106.7
K2-23 Sloped channel - 39.37" (1 m)	75023	75423	12.20	12.40	310	315	13.19	13.39	335	340	12.65	107.8
K2-24 Sloped channel - 39.37" (1 m)	75024	75424	12.40	12.60	315	320	13.39	13.58	340	345	12.87	108.9
K2-25 Sloped channel - 39.37" (1 m)	75025	75425	12.60	12.80	320	325	13.58	13.78	345	350	13.10	110.0
K2-26 Sloped channel - 39.37" (1 m)	75026	75426	12.80	12.99	325	330	13.78	13.98	350	355	13.32	111.1
K2-27 Sloped channel - 39.37" (1 m)	75027	75427	12.99	13.19	330	335	13.98	14.17	355	360	13.56	112.2
K2-28 Sloped channel - 39.37" (1 m)	75028	75428	13.19	13.39	335	340	14.17	14.37	360	365	13.77	113.3
K2-29 Sloped channel - 39.37" (1 m)	75029	75429	13.39	13.58	340	345	14.37	14.57	365	370	13.99	114.4
K2-30 Sloped channel - 39.37" (1 m)	75030	75430	13.58	13.78	345	350	14.57	14.76	370	375	14.22	115.5
<b>K2-030 Constant depth channel - 39.37" (1 m)</b>	<b>75047</b>	<b>75447</b>	<b>13.78</b>	<b>13.78</b>	<b>350</b>	<b>350</b>	<b>14.76</b>	<b>14.76</b>	<b>375</b>	<b>375</b>	<b>14.01</b>	<b>115.5</b>
<b>K2-0303 Constant depth channel - 19.69" (0.5 m)</b>	<b>75048</b>	<b>75448</b>	<b>13.78</b>	<b>13.78</b>	<b>350</b>	<b>350</b>	<b>14.76</b>	<b>14.76</b>	<b>375</b>	<b>375</b>	<b>7.05</b>	<b>68.0</b>
K2-31 Sloped channel - 39.37" (1 m)	75031	75431	13.78	13.98	350	355	14.76	14.96	375	380	14.44	116.6
K2-32 Sloped channel - 39.37" (1 m)	75032	75432	13.98	14.17	355	360	14.96	15.16	380	385	14.67	117.7
K2-33 Sloped channel - 39.37" (1 m)	75033	75433	14.17	14.37	360	365	15.16	15.35	385	390	14.89	118.8
K2-34 Sloped channel - 39.37" (1 m)	75034	75434	14.37	14.57	365	370	15.35	15.55	390	395	15.11	119.9
K2-35 Sloped channel - 39.37" (1 m)	75035	75435	14.57	14.76	370	375	15.55	15.75	395	400	15.34	121.0
K2-36 Sloped channel - 39.37" (1 m)	75036	75436	14.76	14.96	375	380	15.75	15.94	400	405	15.56	122.1
K2-37 Sloped channel - 39.37" (1 m)	75037	75437	14.96	15.16	380	385	15.94	16.14	405	410	15.78	123.2
K2-38 Sloped channel - 39.37" (1 m)	75038	75438	15.16	15.35	385	390	16.14	16.34	410	415	16.02	124.3
K2-39 Sloped channel - 39.37" (1 m)	75039	75439	15.35	15.55	390	395	16.34	16.54	415	420	16.23	125.4
K2-40 Sloped channel - 39.37" (1 m)	75040	75440	15.55	15.75	395	400	16.54	16.73	420	425	16.46	126.5
<b>K2-040 Constant depth channel - 39.37" (1 m)</b>	<b>75049</b>	<b>75449</b>	<b>15.75</b>	<b>15.75</b>	<b>400</b>	<b>400</b>	<b>16.73</b>	<b>16.73</b>	<b>425</b>	<b>425</b>	<b>16.27</b>	<b>126.5</b>
<b>K2-0403 Constant depth channel - 19.69" (0.5 m)</b>	<b>75050</b>	<b>75450</b>	<b>15.75</b>	<b>15.75</b>	<b>400</b>	<b>400</b>	<b>16.73</b>	<b>16.73</b>	<b>425</b>	<b>425</b>	<b>8.14</b>	<b>77.0</b>

Notes:

1. K200 has a galvanized steel edge rail for general use. KS200 has a grade 304 stainless steel edge rail for use where increased aesthetics or corrosion resistance is required.
2. KlassikDrain is sold as channel only.

\* This channel features bottom knockouts; 4" & 6" for 200 mm channels.