

	Part No.		Invert Depth				Overall Depth				Volume	Weight
	K300	KS300	in		mm		in		mm		gal	lbs
			female	male	female	male	female	male	female	male		
K3-00 Constant depth channel - 39.37" (1 m)*	76041	76441	11.81	11.81	300	300	12.80	12.80	325	325	18.01	132.6
K3-1 Sloped channel - 39.37" (1 m)	76001	76401	11.81	12.01	300	305	12.80	12.99	325	330	19.58	132.6
K3-2 Sloped channel - 39.37" (1 m)	76002	76402	12.01	12.20	305	310	12.99	13.19	330	335	20.01	133.8
K3-3 Sloped channel - 39.37" (1 m)	76003	76403	12.20	12.40	310	315	13.19	13.39	335	340	20.44	135.0
K3-4 Sloped channel - 39.37" (1 m)	76004	76404	12.40	12.60	315	320	13.39	13.58	340	345	20.86	136.2
K3-5 Sloped channel - 39.37" (1 m)*	76005	76405	12.60	12.80	320	325	13.58	13.78	345	350	21.28	137.4
K3-6 Sloped channel - 39.37" (1 m)	76006	76406	12.80	12.99	325	330	13.78	13.98	350	355	21.69	138.6
K3-7 Sloped channel - 39.37" (1 m)	76007	76407	12.99	13.19	330	335	13.98	14.17	355	360	22.11	139.8
K3-8 Sloped channel - 39.37" (1 m)	76008	76408	13.19	13.39	335	340	14.17	14.37	360	365	22.51	141.0
K3-9 Sloped channel - 39.37" (1 m)	76009	76409	13.39	13.58	340	345	14.37	14.57	365	370	22.92	142.2
K3-10 Sloped channel - 39.37" (1 m)*	76010	76410	13.58	13.78	345	350	14.57	14.76	370	375	23.32	143.4
K3-010 Constant depth channel - 39.37" (1 m)*	76043	76443	13.78	13.78	350	350	14.76	14.76	375	375	21.22	143.4
K3-0103 Constant depth channel - 19.69" (0.5 m)*	76044	76444	13.78	13.78	350	350	14.76	14.76	375	375	10.61	75.3
K3-11 Sloped channel - 39.37" (1 m)	76011	76411	13.78	13.98	350	355	14.76	14.96	375	380	23.72	144.6
K3-12 Sloped channel - 39.37" (1 m)	76012	76412	13.98	14.17	355	360	14.96	15.16	380	385	24.11	145.8
K3-13 Sloped channel - 39.37" (1 m)	76013	76413	14.17	14.37	360	365	15.16	15.35	385	390	24.51	147.0
K3-14 Sloped channel - 39.37" (1 m)	76014	76414	14.37	14.57	365	370	15.35	15.55	390	395	24.89	148.2
K3-15 Sloped channel - 39.37" (1 m)*	76015	76415	14.57	14.76	370	375	15.55	15.75	395	400	25.27	149.4
K3-16 Sloped channel - 39.37" (1 m)	76016	76416	14.76	14.96	375	380	15.75	15.94	400	405	25.68	150.6
K3-17 Sloped channel - 39.37" (1 m)	76017	76417	14.96	15.16	380	385	15.94	16.14	405	410	26.06	151.8
K3-18 Sloped channel - 39.37" (1 m)	76018	76418	15.16	15.35	385	390	16.14	16.34	410	415	26.44	153.0
K3-19 Sloped channel - 39.37" (1 m)	76019	76419	15.35	15.55	390	395	16.34	16.54	415	420	26.83	154.2
K3-20 Sloped channel - 39.37" (1 m)*	76020	76420	15.55	15.75	395	400	16.54	16.73	420	425	27.21	155.4
K3-020 Constant depth channel - 39.37" (1 m)*	76045	76445	15.75	15.75	400	400	16.73	16.73	425	425	24.53	155.4
K3-0203 Constant depth channel - 19.69" (0.5 m)*	76046	76446	15.75	15.75	400	400	16.73	16.73	425	425	12.27	82.3
K3-21 Sloped channel - 39.37" (1 m)	76021	76421	15.75	15.94	400	405	16.73	16.93	425	430	27.59	156.7
K3-22 Sloped channel - 39.37" (1 m)	76022	76422	15.94	16.14	405	410	16.93	17.13	430	435	27.97	157.9
K3-23 Sloped channel - 39.37" (1 m)	76023	76423	16.14	16.34	410	415	17.13	17.32	435	440	28.34	159.1
K3-24 Sloped channel - 39.37" (1 m)	76024	76424	16.34	16.54	415	420	17.32	17.52	440	445	28.72	160.3
K3-25 Sloped channel - 39.37" (1 m)*	76025	76425	16.54	16.73	420	425	17.52	17.72	445	450	29.09	161.5
K3-26 Sloped channel - 39.37" (1 m)	76026	76426	16.73	16.93	425	430	17.72	17.91	450	455	29.47	162.7
K3-27 Sloped channel - 39.37" (1 m)	76027	76427	16.93	17.13	430	435	17.91	18.11	455	460	29.84	163.9
K3-28 Sloped channel - 39.37" (1 m)	76028	76428	17.13	17.32	435	440	18.11	18.31	460	465	30.21	165.1
K3-29 Sloped channel - 39.37" (1 m)	76029	76429	17.32	17.52	440	445	18.31	18.50	465	470	30.58	166.3
K3-30 Sloped channel - 39.37" (1 m)*	76030	76430	17.52	17.72	445	450	18.50	18.70	470	475	30.95	167.5
K3-030 Constant depth channel - 39.37" (1 m)*	76047	76447	17.72	17.72	450	450	18.70	18.70	475	475	27.87	167.5
K3-0303 Constant depth channel - 19.69" (0.5 m)*	76048	76448	17.72	17.72	450	450	18.70	18.70	475	475	13.94	89.5
K3-31 Sloped channel - 39.37" (1 m)	76031	76431	17.72	17.91	450	455	18.70	18.90	475	480	31.32	168.7
K3-32 Sloped channel - 39.37" (1 m)	76032	76432	17.91	18.11	455	460	18.90	19.09	480	485	31.69	169.9
K3-33 Sloped channel - 39.37" (1 m)	76033	76433	18.11	18.31	460	465	19.09	19.29	485	490	32.06	171.1
K3-34 Sloped channel - 39.37" (1 m)	76034	76434	18.31	18.50	465	470	19.29	19.49	490	495	32.42	172.3
K3-35 Sloped channel - 39.37" (1 m)*	76035	76435	18.50	18.70	470	475	19.49	19.69	495	500	32.79	173.5
K3-36 Sloped channel - 39.37" (1 m)	76036	76436	18.70	18.90	475	480	19.69	19.88	500	505	33.16	174.7
K3-37 Sloped channel - 39.37" (1 m)	76037	76437	18.90	19.09	480	485	19.88	20.08	505	510	33.52	175.9
K3-38 Sloped channel - 39.37" (1 m)	76038	76438	19.09	19.29	485	490	20.08	20.28	510	515	33.88	177.1
K3-39 Sloped channel - 39.37" (1 m)	76039	76439	19.29	19.49	490	495	20.28	20.47	515	520	34.25	178.3
K3-40 Sloped channel - 39.37" (1 m)*	76040	76440	19.49	19.69	495	500	20.47	20.67	520	525	34.61	179.5
K3-040 Constant depth channel - 39.37" (1 m)*	76049	76449	19.69	19.69	500	500	20.67	20.67	525	525	31.25	179.5
K3-0403 Constant depth channel - 19.69" (0.5 m)*	76050	76450	19.69	19.69	500	500	20.67	20.67	525	525	15.63	97.7

Notes

1. K300 has a galvanized steel edge rail for general use. KS300 has a grade 304 stainless steel edge rail for use where increased aesthetics or corrosion resistance is required.
2. KlassikDrain is sold as channel only.

* This channel features bottom knockouts; 6" & 8" for 300 mm channels.