


Type 4010 Constant Depth Channel - 39.37" (1 m)




System 4000 Parts

	Part No.	Price \$	Weight lbs	Pallet Qty
Type 4002 Constant Depth Channel - 39.37" (1 m)	06562	55.00	32.9	28
Type 4000-1 Sloped Channel - 39.37" (1 m)	138001	77.00	32.0	28
Type 4000-2 Sloped Channel - 39.37" (1 m)	138002	77.00	32.9	28
Type 4000-3 Sloped Channel - 39.37" (1 m)	138003	77.00	33.8	28
Type 4000-4 Sloped Channel - 39.37" (1 m)	138004	77.00	34.7	28
Type 4000-5 Sloped Channel - 39.37" (1 m)	138005	77.00	35.6	28
Type 4000-6 Sloped Channel - 39.37" (1 m)	138006	77.00	36.5	28
Type 4000-7 Sloped Channel - 39.37" (1 m)	138007	77.00	37.4	28
Type 4000-8 Sloped Channel - 39.37" (1 m)	138008	77.00	38.3	28
Type 4000-9 Sloped Channel - 39.37" (1 m)	138009	77.00	39.2	28
Type 4010 Constant Depth Channel - 39.37" (1 m)	06561	64.00	40.1	28
Type 4000-0103 Constant Depth Channel - 19.69" (0.5 m) ¹	138033	43.00	23.0	56
Type 4000-10 Sloped Channel - 39.37" (1 m)	138010	77.00	40.1	28
Type 4000-11 Sloped Channel - 39.37" (1 m)	138011	77.00	41.0	28
Type 4000-12 Sloped Channel - 39.37" (1 m)	138012	77.00	41.9	28
Type 4000-13 Sloped Channel - 39.37" (1 m)	138013	77.00	42.8	28
Type 4000-14 Sloped Channel - 39.37" (1 m)	138014	77.00	43.7	28
Type 4000-15 Sloped Channel - 39.37" (1 m)	138015	77.00	44.6	28
Type 4000-16 Sloped Channel - 39.37" (1 m)	138016	77.00	45.5	28
Type 4000-17 Sloped Channel - 39.37" (1 m)	138017	77.00	46.4	28
Type 4000-18 Sloped Channel - 39.37" (1 m)	138018	77.00	47.3	28
Type 4000-19 Sloped Channel - 39.37" (1 m)	138019	77.00	48.2	28
Type 4020 Constant Depth Channel - 39.37" (1 m)	06563	77.00	49.1	28
Type 4000-0203 Constant Depth Channel - 19.69" (0.5 m) ¹	138035	43.00	26.0	56
Type 4000-20 Sloped Channel - 39.37" (1 m)	138020	77.00	49.1	28
Type 4000-21 Sloped Channel - 39.37" (1 m)	138021	77.00	50.0	28
Type 4000-22 Sloped Channel - 39.37" (1 m)	138022	77.00	50.9	28
Type 4000-23 Sloped Channel - 39.37" (1 m)	138023	77.00	51.8	28
Type 4000-24 Sloped Channel - 39.37" (1 m)	138024	77.00	52.7	28
Type 4000-25 Sloped Channel - 39.37" (1 m)	138025	77.00	53.6	28
Type 4000-26 Sloped Channel - 39.37" (1 m)	138026	77.00	54.5	28
Type 4000-27 Sloped Channel - 39.37" (1 m)	138027	77.00	55.6	28
Type 4000-28 Sloped Channel - 39.37" (1 m)	138028	77.00	56.5	28
Type 4000-29 Sloped Channel - 39.37" (1 m)	138029	77.00	57.4	28
Type 4030 Constant Depth Channel - 39.37" (1 m)	138036	77.00	58.0	28
Type 4000-0303 Constant Depth Channel - 19.69" (0.5 m) ¹	138037	43.00	31.0	56
Type 4000-30 Sloped Channel - 39.37" (1 m)	138030	77.00	59.2	28
Closing End Cap	137090	13.00	4.5	-
108-4 4" Outlet Cap	137092	20.00	2.0	-
208-4 4" Outlet Cap	137094	20.00	2.6	-
208-6 6" Outlet Cap	137095	46.00	2.6	-
308-4 4" Outlet Cap	137097	20.00	3.3	-
308-6 6" Outlet Cap	137098	46.00	3.3	-
104-4 Inlet Cap with 4" SCH 40 pipe	137091	31.00	2.6	-
204-4 Inlet Cap with 4" SCH 40 pipe	137093	31.00	3.7	-
204-6 Inlet End Cap with 6" SCH 35 pipe	137099	65.00	3.3	-
In-Line Catch Basin - 19.69" (0.5 m)	05620	121.00	62.0	12
Plastic Catch Basin Trash Bucket	01498	42.00	1.1	-
Installation Device - 4" System	97477	20.00	2.8	-
Removable QuickLok® Bar for Catch Basin	98717	25.00	0.3	-
ACO Seal Polymer Concrete Sealant (10 oz tube)	91120	14.00	1.0	-
SAFETY EDGE CHANNELS & CATCH BASIN				
Type SE4002 Constant Depth Channel - 39.37" (1 m)*	06564	80.00	49.1	28
Type SE4010 Constant Depth Channel - 39.37" (1 m)*	06565	85.00	62.0	12
Type SE4020 Constant Depth Channel - 39.37" (1 m)*	06566	91.00	49.1	28
SE In-Line Catch Basin - 19.69" (0.5 m)*	06567	129.00	62.0	12
QUICKLOK® GRATES & ACCESSORIES				
Galvanized Slotted Grate - 39.37" (1 m) ²	31530	37.00	5.9	200
Galvanized Slotted Grate - 19.69" (0.5 m) ²	31531	18.00	3.0	100
Black Plastic Longitudinal Grate - 19.69" (0.5 m) ^{2,3}	97393	18.00	1.8	400
Gray Plastic Longitudinal Grate - 19.69" (0.5 m) ^{2,3}	97385	18.00	1.8	400
QuickLok® Locking Bar	02899	6.00	0.1	-
QuickLok® Grate Removal Tool	01318	20.00	0.3	-

Galvanized Slotted Grate



Black Plastic Longitudinal Grate



- Bottom knockouts on 0.5 m channels only.
- Load Class A: 3,372 lbs - 116 psi; EN 1433 : 2002 Drainage channels for vehicular and pedestrian areas
- ADA compliant: The Americans with Disabilities Act of 2010, Section 302.3: Where grates are used within walking surfaces, the open slots should be no greater than 0.5" (12.7 mm) wide in one direction. Where the length of the slot is greater than 0.5", the opening should run perpendicular to the main direction of traffic.

* These special products are made to order with variable lead time. Please contact ACO for product-specific information.

Complete Systems

	Price \$/ft	Price \$/m
SYSTEM 4000 COMPLETE SYSTEM		
4002 Channel with Galvanized Slotted Grate	30.34	99.50
4002 Channel with Plastic Grate	30.03	98.50
4010 Channel with Galvanized Slotted Grate	32.93	108.00
4010 Channel with Plastic Grate	32.62	107.00
4020 Channel with Galvanized Slotted Grate	36.74	120.50
4020 Channel with Plastic Grate	36.43	119.50
4000 Sloping Channel with Galvanized Slotted Grate	36.74	120.50
4000 Sloping Channel with Plastic Grate	36.43	119.50
SE4020 Safety Edge Channel with Galvanized Slotted Grate	40.70	133.50
SE4020 Safety Edge Channel with Plastic Grate	40.40	132.50
SE4010 Safety Edge Channel with Galvanized Slotted Grate	39.02	128.00
SE4010 Safety Edge Channel with Plastic Grate	38.72	127.00
SE4002 Safety Edge Channel with Galvanized Slotted Grate	37.50	123.00
SE4002 Safety Edge Channel with Plastic Grate	37.20	122.00